

Digital Output 16-Point Processor (continued)

MU-PDOX02

Electro-Mechanical Relay--240 Vac FTA, 125 Vdc FTA															
Parameter	Specification														
FTA Models	MU-TDOR22, MU-TDOR62														
Outputs	16 isolated Form A (SPST/NO) or Form B (SPST/NC) contacts (jumper selectable per output)														
Contact Type	Silver alloy														
Maximum Load Voltage	265 Vac (rms)/140 Vdc														
Maximum Steady-State Load Current	2.5 A (rms) @ 240 Vac (resistive) per output 2 A @ 30 Vdc (resistive) per output 0.5 A @ 125 Vdc (resistive) per output 1/8 horsepower per output														
Minimum Load Current ⁽¹⁾	100 mA														
Load Surge Current ⁽²⁾	Overload and Endurance per UL 508														
Isolation	1500 Vac rms or ± 1500 Vdc Channel-to-channel, and channel-to-PM/APM/HPM common														
Turn-on Time	10 ms typical, 15 ms maximum														
Turn-off Time	10 ms typical, 15 ms maximum														
Maximum Repetition Rate	360 cycles per hour at rated load														
Contact Life ⁽³⁾	<table border="0"> <thead> <tr> <th>Operations</th> <th>% of Max. Load</th> </tr> </thead> <tbody> <tr> <td>350,000</td> <td>100</td> </tr> <tr> <td>450,000</td> <td>80</td> </tr> <tr> <td>750,000</td> <td>60</td> </tr> <tr> <td>1,000,000</td> <td>40</td> </tr> <tr> <td>1,300,000</td> <td>20</td> </tr> <tr> <td>20,000,000</td> <td>0 (Mechanical Life)</td> </tr> </tbody> </table>	Operations	% of Max. Load	350,000	100	450,000	80	750,000	60	1,000,000	40	1,300,000	20	20,000,000	0 (Mechanical Life)
Operations	% of Max. Load														
350,000	100														
450,000	80														
750,000	60														
1,000,000	40														
1,300,000	20														
20,000,000	0 (Mechanical Life)														
Contact Suppression (Shunt)	51 Ω /0.022 μ F resistor/capacitor snubber across each contact														
Load Fusing on Termination Assembly	3 A 250 V slow-blow (5x20 mm) fuse per output														
Surge withstand capability	ANSI/IEEE C37.90.1-1978														
<p>(1) The power contacts in these relays are not suitable for load currents less than 100 mA.</p> <p>(2) Contact surge rating is limited by fuse opening time. Fuse opening time is 0.5 sec @ 10 A, 1 sec. @ 8 A, 5 sec @ 6 A.</p> <p>(3) For resistive loads (power factor = 1.0); derate linearly by 5% at 0.9 load power factor to 50% at 0.1 load power factor.</p>															